



3750 West Indian School Road
Phoenix, Arizona 85019-3518
(602) 636-6720
(800) 644-9131
(602) 636-6724 Fax

TECHNICAL SHEET

XCELSURFACES X-TEND

DESCRIPTION AND USE

X-TEND admixture is a ready-to-use liquid solution of water reducing polymers and retarding agents. Use **X-TEND** to retard the initial and final set of Xcel Surfaces polymer modified overlayments during hot weather placement. **X-TEND** is safe to the touch and easy to use.

ADVANTAGES

- Easy to use
- Very predictable performance
- Cost effective
- Increases ultimate strengths of overlayment

SPECIFICATIONS

Typical properties of **X-TEND**:

Appearance:	Translucent Violet
Specific gravity:	1.04
Weight per gallon:	9.85 lbs.

ADDITION RATES AND METHOD

X-TEND can be added within a range of 1 to 10 fluid ounces per 50 lbs. of Xcel Surfaces overlayment powder. The dosage used will be dictated by the degree of retardation needed by the specific job conditions. **X-TEND** should be added at the start of the mixing procedure. Later addition of the retarder will greatly reduce the effectiveness of the product.

CAUTION

Using more than the recommended dosage may cause the overlayment to fail to set properly. Stay within the dosage guidelines.

PACKAGING

1 gallon and 5 gallons

Xcel Surfaces – standard product warranty:

To the best of our knowledge, the information contained herein is accurate. The warranty described herein shall be in lieu of any other warranty, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose. There are no warranties that extend beyond the description of the face hereof. The buyer's sole and exclusive remedy against Seller shall be for the replacement of the products or refund of the purchase price in the event that a defective condition of the products should be found to exist. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to the Buyer. The sole purpose of this exclusive remedy shall be to provide Buyer with replacement of the products or refund of the purchase price of the products if any defect in materials or workmanship is found to exist. The exclusive remedy shall not be deemed to have its essential purpose so long as Seller is willing and able to replace the defective products or refund the purchase price. Buyer must give Seller notice in writing of any alleged defect covered by this warranty (together with all identifying details, including Product Code(s), description, lot number and date of purchase, within thirty (30) days of the discovery of the defect. Final determination of the suitability of the material for use contemplated, the manner of use, and whether the suggested use infringes any patents, is the sole responsibility of the Buyer.

READ M.S.D.S. BEFORE USE

Dispose of any unwanted material in accordance with FEDERAL, STATE and LOCAL regulations.

Xcel Surfaces products are intended for professional use only. Keep away from children.

Xcel Surfaces warrants its products to be free of manufacturing defects and that they will meet the current published physical properties when applied in accordance with Xcel Surfaces directions and tested in accordance with ASTM and Xcel Surfaces standards. There are no other warranties by Xcel Surfaces of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Xcel Surfaces shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any cause whatsoever. Xcel Surfaces shall also not be responsible for use of this product in a manner to infringe on any patent held by others.