3750 West Indian School Road
Phoenix, Arizona 85019-3518
(602) 636-6720
(800) 644-9131
(602) 636-6724 Fax
www.xcelsurfaces.com

TECHNICAL DATA SHEET- XCEL GRIP

DESCRIPTION AND USE
XCEL GRIP is a lightweight, durable, slip resistant additive used with Xcel Surfaces. Use in clear or pigmented, anti-skid, textured coatings.

FEATURES
XCEL GRIP is an easy-to-use lightweight optically clear polycarbonate that is used to reduce slippery situations in wet areas or inclines.

APPLICATION
XCEL GRIP is versatile enough to be applied either dry or wet. For large areas such as floors, **XCEL GRIP** can be broadcast dry over a pre-wetted surface, or it can be mixed with the vehicle and then sprayed, brushed, or rolled onto a dry surface.

TECHNICAL DATA
Specific Gravity (H20=1)……………………………1.34
Density (lbs. per gal)………………………………10.90
Color (in dispersion)………………………….……clear
Color (in raw form)…………………………………white

MIXING INSTRUCTIONS
Add 3-4 ounces of **XCEL GRIP** per gallon. Stir well.

PACKAGING
16 oz container

HANDLING & STORAGE
Read Material Safety Data Sheets before using. Dispose of unused material in accordance with Federal, State and Local regulations.

Xcel Surfaces Grip