

3750 West Indian School Road Phoenix, Arizona 85019-3518 (602) 636-6720 (800) 644-9131 (602) 636-6724 Fax www.xcelsurfaces.com

TECHNICAL DATA SHEET- VERSA TIQUE

DESCRIPTION AND USE

XCEL SURFACES VERSA TIQUE Cementitous Antiquing Product is a versatile coloring agent that can be easily applied and will hold fast to any textured concrete surface. VERSA TIQUE is sold as a powder, but is designed to be mixed with water and applied as a liquid wash coat. VERSA TIQUE can be used to revitalize a weathered concrete surface or add an antique color to a freshly textured surface. It goes on quickly and easily and can be removed readily for greater control of the coloring process. This product is water-based.

APPLICATION

Xcel Surfaces VERSA TIQUE is easy to mix and apply so it can be used by professionals and do-ityourselfers alike. It comes in a 1 gallon pail with approximately 3 pounds of colored powder and a three-guarter cup measuring spoon wrapped in a plastic bag. To mix: pull out and open the bag of VERSA TIQUE powder, fill the 1 gallon pail with water, and mix in one full three-quarter cup measuring spoon of the powder. Use more or less of the product in one gallon of water to achieve different results in color intensity. VERSA TIQUE can be mixed readily with a stir stick so motorized mixing is not necessary, but the product in the container will need to be agitated periodically during application to keep the solids from settling. This settling property of VERSA **TIQUE** is important in reaching the desired antique effect. Before applying product to unsealed concrete, it is helpful to pre-moisten the surface with water so the liquid color will have time to even out and settle properly. The most basic technique to apply VERSA **TIQUE** is to simply pour the liquid color straight onto the horizontal concrete surface with a standard garden watering can, make sure to leave a uniform coat of liquid over the area to be covered. If Necessary, liquid VERSA TIQUE can be spread quickly and easily with a clean push broom. Be sure to have clean water handy to spray while it is still wet and can be wiped of clean dry sponge when dry.

FEATURES

- Mess Free- no power washing less clean up time
- Complete control of antiquing process
- Use Multiple colors for more natural look

SEALING AND MAINTENANCE

A quality Xcel Surfaces sealer is recommended to protect the newly textured or colored concrete surface. The concrete must be cleaned and thoroughly dried prior to application.

COVERAGE

One 3 pound bucket of Xcel Surfaces **VERSA TIQUE** covers about 2000-3000 square feet.

PACKAGING

1 gallon

HANDLING & STORAGE

Read Material Safety Data Sheets before using. Dispose of unused material in accordance with Federal, State and Local regulations. Storage temperature below: (120° F).

Xcel Surfaces products are intended for professional use only. Keep away from children. Xcel Surfaces warrants its products to be free of manufacturing defects and that they will meet the current published physical properties when applied in accordance with Xcel Surfaces directions and tested in accordance with ASTM and Xcel Surfaces standards. There are no other warranties by Xcel Surfaces of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Xcel Surfaces shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any cause whatsoever. Xcel Surfaces shall also not be responsible for use of this product in a manner to infringe on any patent held by others.

> © XCEL SURFACES 2008 All rights reserved. Made in the USA