



3750 West Indian School Road
Phoenix, Arizona 85019-3518
(602) 636-6720
(800) 644-9131
(602) 636-6724 Fax
www.xcelsurfaces.com

TECHNICAL DATA SHEET- X-TEND

DESCRIPTION AND USE

X-TEND admixture is a ready-to-use liquid solution of water reducing polymers and retarding agents. Use X-TEND to retard the initial and final set of Xcel Surfaces polymer modified overlayments during hot weather placement. X-TEND is safe to touch and easy to use.

ADVANTAGE

- Easy to use
- Very predictable performance
- Cost effective
- Increase ultimate strengths of overlayment

SPECIFICATIONS

Typical properties of X-TEND:

Appearance.....Translucent Violet
 Specific Gravity.....1.04
 Weight per gallon.....9.85 lbs

ADDITION RATES AND METHOD

X-TEND can be added within a range of 1 to 10 fluid ounces per 50 lbs. of Xcel Surfaces overlayment powder. The dosage used will be dictated by the degree of retardation needed by the specific job conditions. X-TEND should be added at the start of the mixing procedure. Later addition of the retarder will greatly reduce the effectiveness of the product.

CAUTION

Using more than the recommended dosage may cause the overlayment to fail to set properly. Stay within the dosage guidelines.

PACKAGING

1 gallon

HANDLING & STORAGE

Read Material Safety Data Sheets before using. Dispose of unused material in accordance with Federal, State and Local regulations. Storage temperature: (45°-85° F). Do not let Product Freeze.

Xcel Surfaces products are intended for professional use only. Keep away from children. Xcel Surfaces warrants its products to be free of manufacturing defects and that they will meet the current published physical properties when applied in accordance with Xcel Surfaces directions and tested in accordance with ASTM and Xcel Surfaces standards. There are no other warranties by Xcel Surfaces of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Xcel Surfaces shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any cause whatsoever. Xcel Surfaces shall also not be responsible for use of this product in a manner to infringe on any patent held by others.

© XCEL SURFACES 2008
All rights reserved. Made in the USA

Xcel Surfaces X-Tend